

EPITA - Practical Programming



03 - Structures

A word on malloc(3)

```
#include <err.h>
#include <stdlib.h>

int main()
{
    int *p1 = malloc(sizeof (int));
    if (p1 == NULL) // handle error !
        err(1, "malloc failed");
    int *p2 = calloc(42, sizeof (int));
    if (p2 == NULL) {
        free(p1);
        err(1, "calloc failed");
    }
    int *p3 = realloc(p2, 64 * sizeof (int));
    if (!p3) {
        free(p1);
        free(p2);
        err(1, "realloc failed");
    }
    p2 = p3;
    free(p1);
    free(p2);
    return 0;
}
```

Data Structures



Data Structures

A good program is first good data structures and
then, eventually good code.



Struct



struct

- C struct are basic block of data
- Fields accesses are resolved at compile-time
- Layout and size are as important as field names

Anonymous Struct

```
#include <stdio.h>
int main() {
    // No need for type definitions
    struct { int a,b; float c,d; } s =
        { 42, 0, 3.14, 1.414 };
    printf("a = %d\n", s.a);
    printf("b = %d\n", s.b);
    printf("c = %g\n", s.c);
    printf("d = %g\n", s.d);
    return 0;
}
```

Named Struct

```
// Fake struct definition
struct my_struct {
    int             a,b;
    float          c,d;
};

// struct def is now known
float f(struct my_struct s) {
    return s.a + s.b + s.c + s.d;
}
```

Struct As Argument Or Result

- A struct is a block of data
- When passed without pointer, struct are copied
- When returned without pointer, they are copied

```
struct my_struct build() {  
    struct my_struct s =  
        { 42, 0, 3.14, 1.414 };  
    return s;  
}
```

```
float g() {  
    struct my_struct s1, s2;  
    s1 = build();  
    s2 = s1;  
    return f(s2);  
}
```

Struct Through a Pointer

```
void display(struct my_struct *s) {  
    printf("{\\n");  
    printf("  a = %d; \\n", s->a);  
    printf("  b = %d; \\n", s->b);  
    printf("  c = %g; \\n", s->c);  
    printf("  d = %g; \\n", s->d);  
    printf("}\\n");  
}
```

Struct Layout

- Fields may be aligned, leaving gaps in the struct
- Alignment depends on data size and word size
- Basic rule: a field start on an address multiple of its size.

Struct Layout

```
#include <stddef.h>
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>

struct demo
{
    uint8_t f1;
    uint64_t f8;
    uint32_t f4;
};

int main()
{
    printf("sizeof (struct demo) = %zu\n", sizeof (struct demo));
    printf("Layout:\n");
    printf("    f1: %zu\n", offsetof(struct demo, f1));
    printf("    f8: %zu\n", offsetof(struct demo, f8));
    printf("    f4: %zu\n", offsetof(struct demo, f4));
    return 0;
}
```

Struct Layout

In 64bit:

```
sizeof (struct demo) = 24
```

Layout:

f1:	0
-----	---

f8:	8
-----	---

f4:	16
-----	----

In 32bit:

```
sizeof (struct demo) = 16
```

Layout:

f1:	0
-----	---

f8:	4
-----	---

f4:	12
-----	----

Arrays In Struct

```
struct s_user {  
    unsigned          uid, gid;  
    char             login[16];  
};  
  
int main() {  
    struct s_user      u;  
    printf("u.login:\t%p\n",u.login);  
    printf("&(u.login):\t%p\n",&(u.login));  
    return 0;  
}
```

Arrays In Struct

u.login:	0x7ffffed0045b0
&(u.login):	0x7ffffed0045b0

More examples

```
struct user
{
    unsigned uid, gid;
    char login[16];
};

/* arrays of structs */
struct user* find_user(struct user users[], size_t len, unsigned uid)
{
    struct user *cur = users;
    for (; cur != users + len && cur->uid != uid; cur++)
        continue;
    return cur;
}
```

More examples

```
/* vectors */
struct vector
{
    size_t capacity, size;
    int *store;
};

/* matrix */
struct matrix
{
    size_t w, h;
    double *mat;
};
```

Recursive Structure

```
struct list {  
    struct list *next;  
    int value;  
};
```

Lists

Linked Lists

- Classical data structure
- Easy to implement
- Heavily use pointers
- Base structure for queues and stacks

Lists

```
struct list {  
    struct list *next;  
    int value;  
};  
  
struct list *empty_list() { return NULL; }  
  
int list_is_empty(struct list *l) {  
    return l == NULL;  
}
```

Adding Elements

```
struct list *add(struct list *l, int x) {  
    struct list           *tmp;  
    // Size DOES matter !  
    tmp = malloc(sizeof (struct list));  
    tmp->value = x;  
    tmp->next = l;  
    return tmp;  
}
```

Altering The Head

```
// Note the double * on l
void addin(struct list **l, int x) {
    struct list           *tmp;
    tmp = malloc(sizeof (struct list));
    tmp->value = x;
    tmp->next = *l;
    *l = tmp;
}
```

Classical Loop On List

```
for (; l; l = l->next) {  
    // work on element  
}
```

List Length


```
size_t list_len(struct list *l) {  
    size_t len;  
    for (len=0; l; l = l->next)  
        len += 1;  
    return len;  
}
```

Sentinel

Goal: remove corner cases and double pointers

- add a fake node at the beginning of the list

Sentinel



Example

```
void list_remove(struct list **list, struct list *elm)
{
    struct list *cur = *list;
    struct list *prev = NULL;
    for (; cur != elm; cur = cur->next)
        prev = cur;
    if (prev == NULL)
        *list = cur->next;
    else
        prev->next = cur->next;
}
```

```
void list_remove(struct list **list, struct list *elm)
{
    if (*list == elm) {
        *list = elm->next;
        return;
    }
    struct list *cur = *list;
    for (; cur->next != elm; cur = cur->next)
        continue;
    cur->next = elm->next;
}
```

Sentinel - example

```
void list_remove(struct list **list, struct list *elm)
{
    struct list *cur = *list;
    struct list *prev = NULL;
    for (; cur != elm; cur = cur->next)
        prev = cur;
    if (prev == NULL)
        *list = cur->next;
    else
        prev->next = cur->next;
}
```

```
void list_remove(struct list *list, struct list *elm)
{
    for (; list->next != elm; list = list->next)
        continue;
    list->next = elm->next;
}
```

Another solution

```
void list_remove(struct list **list, struct list *elm)
{
    struct list **ref = list;
    for (; *ref != elm; ref = &((*ref)->next))
        continue;
    *ref = elm->next;
}
```


Queue



Classic Queue

```
struct queue {  
    struct queue *next;  
    void        *value;  
};  
  
struct queue* queue_empty(void) { return NULL; }  
  
int queue_is_empty(struct queue *q) { return q == NULL; }
```

Circular Lists as Queue



Queue Push

```
struct queue* queue_push(struct queue *q, void *x) {
    struct queue *tmp;
    tmp = malloc(sizeof (struct queue));
    tmp->value = x;
    if (q) {
        tmp->next = q->next;
        q->next = tmp;
    } else {
        tmp->next = tmp;
    }
    return tmp;
}
```

Queue Pop

```
void* queue_pop(struct queue **q) {
    struct queue *tmp = (*q)->next;
    void         *x   = tmp->value;
    if (tmp == tmp->next)
        *q = NULL;
    else
        (*q)->next = tmp->next;
    free(tmp);
    return x;
}
```

Trees



Binary Trees

```
struct tree {  
    // Children  
    struct tree  
        // Content  
        int  
    };  
        *left, *right;  
        key;
```

Binary Tree

```
// Compute size
size_t tree_size(struct tree *t) {
    if (t == NULL)
        return 0;
    return 1 + tree_size(t->left) + tree_size(t->right);
}

// Compute height
static inline int max(int a, int b) { return a > b ? a : b; }

int tree_height(struct tree *t) {
    if (t == NULL)
        return -1;
    return 1 + max(tree_height(t->left), tree_height(t->right));
}
```

Binary Tree

```
// Prefix print
void prefix_print(struct tree *t) {
    if (t) {
        printf("%d; ", t->key);
        prefix_print(t->left);
        prefix_print(t->right);
    }
}
```

Binary Tree

```
// Breadth first print
void breadth_print(struct tree *t) {
    if (t) {
        struct queue      *q = queue_empty();
        q = queue_push(q, t);
        q = queue_push(q, NULL);
        do {
            t = queue_pop(&q);
            if (t == NULL) {
                printf("\n");
                if (!queue_is_empty(q))
                    q = queue_push(q, NULL);
            } else {
                printf("%d ", t->key);
                if (t->left)
                    q = queue_push(q, t->left);
                if (t->right)
                    q = queue_push(q, t->right);
            }
        } while (!queue_is_empty(q));
    }
}
```